


6474

Design By Sebastian Herkner

The glass shade pendant features an open metal frame imbedded with LEDs that contains a cylindrical diffuser made of mouthblown opaline glass. It floats from nearly invisible overhead cables, generating a warm, 360-degree glow as if from a fire.

Model Sheet



Optional: Extra cable length
Min. quantity, upcharge and extra lead time apply [EN]

Finish  11 Black
NCS S 8500-N

LED temperature color 2200 K / 2700 K / 3000 K / 4000 K
Optional 2200 K / 2700 K / 3000 K / 4000 K
Min. quantity, upcharge and extra lead time apply [EN]

Dimming DALI / 1-10V / Casambi / Push

Installation type Wall mount


Materials Body: Aluminum
Shade: opal triplex glass
Driver box: Aluminum

Light source 1 x LED STRIP 20,8W 750mA



LED CRI>90 2165 lm 104
2200 K / 2700 K / 3000 K / 4000 K

Driver Constant Current 750 90~305
V V 50~60 Hz HZ




Application Hanging lamps

Packaging 1 Box
1,132 m x 0,3 m x 0,3 m
Gross weight 9,5
Net weight 7
Vol. 0.1018

Lighting effect

General Lighting


Lamp for general lighting that equally distributes the light in all directions.



Photometric Data

Efficiency 41.96 lm/W
Coordinate System CG
Total Flux 1034.74 lm
Maximum Value 171.64 cd

Other Applications




6476

Design By Sebastian Herkner

The glass shade pendant features an open metal frame imbedded with LEDs that contains a cylindrical diffuser made of mouthblown opaline glass. It floats from nearly invisible overhead cables, generating a warm, 360-degree glow as if from a fire.

Model Sheet



Optional: Extra cable length
Min. quantity, upcharge and extra lead time apply [EN]

Finish	11 Black NCS S 8500-N
LED temperature color	2200 K / 2700 K / 3000 K / 4000 K Optional 2200 K / 2700 K / 3000 K / 4000 K Min. quantity, upcharge and extra lead time apply [EN]
Dimming	Casambi / Push / DALI / 1-10V
Installation type	Wall mount
Materials	Body: Aluminum Shade: opal triplex glass Driver box: Aluminum
Light source	1 x LED STRIP 27,9W 750mA E
LED	CRI>90 2907 lm 104 2200 K / 2700 K / 3000 K / 4000 K
Driver	Constant Current 750 90~305 V V 50~60 Hz HZ Dimmable LED IP20 Multi-volt 50-60Hz TRIAC 1-10V
Application	Hanging lamps
Packaging	1 Box 1,43 m x 0,3 m x 0,3 m Gross weight 11 Net weight 8 Vol. 0.1287

Lighting effect


General Lighting

Lamp for general lighting that equally distributes the light in all directions.

Photometric Data

Efficiency	41,96 lm/W
Coordinate System	CG
Total Flux	1338,37 lm
Maximum Value	222,01 cd

Other Applications



All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty

Vibia Lighting, S.L.U.

Office / Oficina
Progrés 4-6. 08850 Gavà. Barcelona, Spain.

International T +34 934 796 971
Spain / Portugal T +34 934 796 970

customer.service@vibia.com
vibia.com